

DATA SHEET

Industrial cable reel

2 Israeli sockets with protective caps, RCCB, MCB, cable with Israeli plug

- For use when required several outlets remote from an existing electrical outlet.
- Suitable for professionals use when required greater electrical capacity and mechanical strength
- Equipped with RCCB (2P 6kA 40A), with CB certification, for protection against electric shock Type A 30mA
- The product is equipped with MCB (1P 6kA 16A), with CB certification, for protection against overload
- Indication Light for distinguishing Operating mode and disconnect
- Extremely durable cable reel suitable for hard Fieldwork.
- The reel is made from high quality and durable plastic
- The reel frame of is made of particularly robust galvanized steel
- The product is equipped with an easy to use scroll handle.

Max operation voltage: 230VAC

Max current: 16A

Poles: 2P+E (Phase L, Neutral N, Earth PE)

IP rate: IP20

Materials:

Cable reel Body: PP Polypropylene

Cable reel frame: St+ plating

Handle: rubber

Socket: Nylon66

Pins and Socket contacts: Brass (approx. 70% copper)

Socket type: 2 Israeli sockets

Plug type: Israeli plug Model ILP4

RCCB: 2P 6kA 40A Type A 30mA

MCB: 1P 6kA 16A

Compatible Countries: Israel, Palestine.



PRODUCTS:



PVC Cable Double layer (HO5VV-F)

Double insulated cable (double layer of PVC) with electric capacity and greater mechanical strength

Product No.	Model	Cable length	Cable type	Cable color	Unit weight	QTY in carton
DCR32525261	DCRP-25RD	25 m	3X2.5mm ²	Orange	7.9	1
DCR32540262	DCRP-40RD	40 m	3X2.5mm ²	Orange	10.75	1
DCR32550263	DCRP-50RD	50 m	3X2.5mm ²	Orange	12.65	1



Polyurethane Cable (HO7BQ-F)

Suitable for high performance electrical cables in the most challenging of environments. It is very flexible throughout a broad temperature range.

Product No.	Model	Cable length	Cable type	Cable color	Unit weight	QTY in carton
DCR32525279	DCRP-25RP	25 m	3X2.5mm ²	Orange	8	1
DCR32540280	DCRP-40RP	40 m	3X2.5mm ²	Orange	11	1
DCR32550281	DCRP-50RP	50 m	3X2.5mm ²	Orange	13	1

Neoprene cable (HO7RNF)

- Suitable for medium mechanical loads in dry, damp or wet area
- Flexibility and mechanical strength exceptions, resistant to abrasion.
- Resistant to extreme temperatures: • in motion -25°C up to 90°C • In fixed installation -40°C up to 90°C

Product No.	Model	Cable length	Cable type	Cable color	Unit weight	QTY in carton
DCR32525221	DCRP-25RN	25 m	3X2.5mm ²	Orange	8.2	1
DCR32540249	DCRP-40RN	40 m	3X2.5mm ²	Orange	11.35	1
DCR32550222	DCRP-50RN	50 m	3X2.5mm ²	Orange	13.65	1

DRAWINGS: (mm)

