

## DATA SHEET

**Industrial cable reel****2 Israeli sockets with protective caps,  
3X16A CEE Plug**

- For use when required several outlets remote from an existing electrical outlet.
- Suitable for professionals use when required greater electrical capacity and mechanical strength
- Indication Light for distinguishing Operating mode and disconnect
- Extremely durable cable reel suitable for hard Fieldwork
- The reel is made from high quality and durable plastic
- The reel frame of is made of particularly robust galvanized steel
- The product is equipped with an easy to use scroll handle

**Max operation voltage:** 230VAC

**Max current:** 16A

**Poles:** 2P+E (Phase L, Neutral N, Earth PE)

**IP rate:** IP20

**Materials:**

Cable reel Body: PP Polypropylene

Cable reel frame: St+ plating

Handle: rubber


Socket: Nylon66

Pins and Socket contacts: Brass (approx. 70% copper)

**Socket type:** 2 Israeli sockets

**Plug type:** Israeli plug Model ILP4

**Compatible Countries:** Israel, Palestine.

**PRODUCTS:****PVC Cable Double layer (HO5VV-F)**

Double insulated cable (double layer of PVC) with electric capacity and greater mechanical strength

Product No.	Model	Cable length	Cable type	Cable color	Unit weight	QTY in carton
DCR32525491	DCRP-25CD	25 m	3X2.5mm <sup>2</sup>	Orange	7.65	1
DCR32540492	DCRP-40CD	40 m	3X2.5mm <sup>2</sup>	Orange	10.5	1
DCR32550493	DCRP-50CD	50 m	3X2.5mm <sup>2</sup>	Orange	12.4	1



## Polyurethane Cable (HO7BQ-F)

Suitable for high performance electrical cables in the most challenging of environments. It is very flexible throughout a broad temperature range.

Product No.	Model	Cable length	Cable type	Cable color	Unit weight	QTY in carton
DCR32525497	DCRP-25CP	25 m	3X2.5mm <sup>2</sup>	Orange	8	1
DCR32540498	DCRP-40CP	40 m	3X2.5mm <sup>2</sup>	Orange	11	1
DCR32550499	DCRP-50CP	50 m	3X2.5mm <sup>2</sup>	Orange	13	1

## Neoprene cable (HO7RNF)

- Suitable for medium mechanical loads in dry, damp or wet area
- Flexibility and mechanical strength exceptions, resistant to abrasion.
- Resistant to extreme temperatures: • in motion -25°C up to 90°C • In fixed installation -40°C up to 90°C

Product No.	Model	Cable length	Cable type	Cable color	Unit weight	QTY in carton
DCR32525494	DCRP-25CN	25 m	3X2.5mm <sup>2</sup>	Orange	7.95	1
DCR32540495	DCRP-40CN	40 m	3X2.5mm <sup>2</sup>	Orange	11.1	1
DCR32550496	DCRP-50CN	50 m	3X2.5mm <sup>2</sup>	Orange	13.2	1

### DRAWINGS: (mm)

