

DATA SHEET

Industrial cable reel

4 Israeli sockets with protective caps, cable with Israeli plug

- For use when required several outlets remote from an existing electrical outlet.
- Suitable for professionals use when required greater electrical capacity and mechanical strength
- Indication Light for distinguishing Operating mode and disconnect
- Extremely durable cable reel suitable for hard Fieldwork
- The reel is made from high quality and durable plastic
- The reel frame of is made of particularly robust galvanized steel
- The product is equipped with an easy to use scroll handle

Max operation voltage: 230VAC

Max current: 16A

Poles: 2P+E (Phase L, Neutral N, Earth PE)

IP rate: IP20

Materials:

Cable reel Body: PP Polypropylene

Cable reel frame: St+ plating

Handle: rubber

Socket: Nylon66

Pins and Socket contacts: Brass (approx. 70% copper)

Socket type: 4 Israeli sockets

Plug type: Israeli plug Model ILP4

Compatible Countries: Israel, Palestine.



PRODUCTS:



16A

230
VAC

3x2.5
mm²

IP20



PVC Cable Double layer (HO5VV-F)

Double insulated cable (double layer of PVC) with electric capacity and greater mechanical strength

Product No.	Model	Cable length	Cable type	Cable color	Unit weight	QTY in carton
DCR32525473	DCRP-25QD	25 m	3X2.5mm ²	Orange	7.7	1
DCR32540474	DCRP-40QD	40 m	3X2.5mm ²	Orange	10.55	1
DCR32550475	DCRP-50QD	50 m	3X2.5mm ²	Orange	12.45	1



Polyurethane Cable (HO7BQ-F)

Suitable for high performance electrical cables in the most challenging of environments. It is very flexible throughout a broad temperature range.

Product No.	Model	Cable length	Cable type	Cable color	Unit weight	QTY in carton
DCR32525476	DCRP-25QP	25 m	3X2.5mm ²	Orange	8	1
DCR32540477	DCRP-40QP	40 m	3X2.5mm ²	Orange	11	1
DCR32550478	DCRP-50QP	50 m	3X2.5mm ²	Orange	13	1

Neoprene cable (HO7RNF)

- Suitable for medium mechanical loads in dry, damp or wet area
- Flexibility and mechanical strength exceptions, resistant to abrasion.
- Resistant to extreme temperatures: • in motion -25°C up to 90°C • In fixed installation -40°C up to 90°C

Product No.	Model	Cable length	Cable type	Cable color	Unit weight	QTY in carton
DCR32525437	DCRP-25QN	25 m	3X2.5mm ²	Orange	8	1
DCR32540442	DCRP-40QN	40 m	3X2.5mm ²	Orange	11.15	1
DCR32550438	DCRP-50QN	50 m	3X2.5mm ²	Orange	13.25	1

DRAWINGS: (mm)

