deko

DATA SHEET

USB Charger Keystone 10W 2.1A

- Fast charging solution for electronic devices such as Mobile phones, Tablets, Media players etc.
- Installation by snap into keystone compatible components: wall plate, face plate, surface-mount box, or a patch panel.
- Built in TEXAS
 Built in TEXAS
 Built in TEXAS
 Controller for supporting advance charging protocols, with an auto-detect feature monitors USB data line voltage and automatically provides the correct electrical signatures on the data lines to charge compliant devices.
- Charging indication: Blue LED light in 100 mA charging.
- Connection: 2 wires connection (Phase L, Neutral N).

INPUT:

Input Voltage: 85VAC -265VAC Switching Frequency: 50K Hz~100K Hz Efficiency &: 70% min at 220VAC standby power: 0.6W max at 220VAC **OUTPUT:**

Output Voltage: 5.1VDC Max Charging Load: 2A ± 2% 10W

SUPPORT FEATURES:

SDP (USB 2.0), SDP (USB 3.0), CDP, DCP

PROTECTION:

Cooling: Self-cooling

Short Protection: 85V at 265VAC

TOPOLOGY:

Topology: Single-ended fly back

TESTING:

MTBF (mean time between failures): 100,000 Hours under 25°C

TEMPERATURE:

-10°C to 40°C





SMART USB keystone charger 2.1A White

5.1 Vdc

2A

IEC

62368

CR



SDP

DCP

SDP

PRODUCTS:

Product No.	Model	Name	Color	Unit weight	Unit packing	QTY in carton
DKJUSBW0003	USBC2.1	USB Keystone Charger 2.1A	White	0.1Kg	Box	10
DKJUSBW0009	USBC2.1	USB Keystone Charger 2.1A	Black	0.1Kg	Box	10

DRAWINGS: (mm)







